KIKKO MAX L250U3:KikkoMax UK 21-06-2010 10:42 Pagin





KIKKO MAX



NECTA

Kikko Max is the free standing vending machine with a 620 cup capacity and up to 7 canisters which complements the Necta Hot & Cold range. With a height of 1830 mm, it has been designed to stand alongside the similarly sized Snakky Max or Sfera machines. The Kikko Max works in a master/salve mode and utilizes a single payment system which provides "One-Stop-Shopping" and creates an appealing machine bank, ensuring the most user friendly and practical vending service available.

ELECTRONIC CONTROL

The 16-bit electronic control with incorporated flash EPROM is extremely flexible and complete, as well as being compatible with the PC application GIGA. This allows a palmtop to be connected, via an RS232 interface, to allow the automatic set-up of the machine as well as the downloading of sales statistics and data (also in EVA-DTS format). With GIGA it is also possible to have remote monitoring of the machine using GSM technology.

PAYMENT SYSTEMS

Kikko Max is pre-set for the installation of systems with Executive, BDV and MDB protocol as well as for installation of validators.

At the same time, the following can be fitted:

- Change-giver, validator or coin mechanism
- Bill acceptor
- Cashless system with key or card.

ACCESSORIES

Mechanical selections counter kit Lid for coin box kit Cup sensor + cup station lamp kit Cup station lamp kit 20 litre water tank kit 2x20 litre water tanks kit Still cooling unit kit (for powders) Master/slave kit RS232 jack kit GSM kit





Optimu	ım interna	l acces	iS
Z 3000	patented	coffee	group

POWER CONSUMP	TION
sso version	

To reach operating temperature 100 Wh For each hour of stand-by Instant version To reach operating temperature For each hour of stand-by

CAPACITY			
Cups (Ø 70-71 mm)	620*		
Stirrers (length 95/105 mm)	550		
Containers	6 ES / 7 IN		
Espresso boiler	0.61		
Instant boiler	21		
Coffee beans	3.2 kg		
Instant coffee	0.9 kg ES / 1.2 kg IN		
Chocolate	5.2 kg		
Milk	2.6 kg		
Tea	3.2 kg		
Sugar	4 kg		
*166 cc			

CHARACTERISTICS		
Height	1830 mm*	
Width	540 mm	
Depth	650 mm	
Overall depth with door open	1120 mm	
Weight	126 kg ca.	
Power supply voltage	230 V	
Power supply frequency	50 Hz	
Installed power	1800 W	
Water mains pressure (With 3/4" gas male connection)	0.5 to 8.5 bar	
(With 3/4" gas male connection) \ *Adjustable feet: +10 -10 mm		



FXAMPI	ES OF PO	SSIBLE CO	INFIGURATION	S

	KIKKO MAX ES 6 (Espresso Unit + 5 canisters)	KIKKO MAX IN 7 (7 canisters)
Pre-selections		
Sugar dosing	₽	<u></u>
Bean coffee black	.	
Bean coffee long	<u>=</u>	
Bean café au lait	■	
Bean coffee white	<u>=</u> :	
Instant espresso coffee		<u>=</u>
Coffee long		<u>=</u>
Café au lait		<u>=</u>
Coffee white		<u>=</u>
Cappuccino		<u> </u>
Chocolate	<u>=</u> :	<u>=</u>
Chocolate strong	<u>=</u> :	<u></u>
Chocomilk	■:	<u>=</u> :
Decaf/Instant coffee black	■:	<u>=</u>
Decaf/Instant coffee long	■	<u></u>
Decaf/Instant café au lait	<u>=</u> :	<u> </u>
Decaf/Instant cappuccino	<u>=</u> :	<u></u>
Lemon tea	<u>=</u> :	<u>=</u> :
Soup		<u> </u>
Milk/Hot water	■:	<u></u>
Cup only	<u>=</u>	<u>=</u>
No cup	■	

N&W GLOBAL VENDING S.p.A.

Via Roma, 24 24030 Valbrembo (BG) Italy Tel. +39 035 606111 - Fax +39 035 606519









N&W Global Vending reserves the right to alter specifications without notice

www.nwglobalvending.com