

I

0









ENERGY-SAVING LED LIGHTING



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



A coffee... with style

This range represents the perfect combination of technological innovation and special features with an elegant and modern finishing. Available in different configurations, Coffeemar Bluetec stands out for its new aluminium boiler and its product selection touch keyboard, as well as for its striking new look and improvements in design, labels and lighting. It is the most versatile and reliable model, suitable for any location thanks to its innovative design with a finish of stainless steel and glass.

FEATURES

- Pressure valve in the brewing unit to keep constant pressure during the complete brewing cycle.
- Motorised water distributor without electrovalves.
- Aluminium boiler with resistor and capped probes, with no contact with the water (avoiding o-rings and calcium oxide formation).
- Two cup-dispenser models, depending on the cup diameter (65-67 mm or 67-69 mm).
- Adjustable stir-stick dispenser, between 75 mm and 115 mm long.
- Self-cleaning of mixing bowls, product exit and grinder assembly: manual or automatic (programmable).
- Anti-steam sugar-adding system directly into the cup.
- Continuous temperature control of the water in the boiler.
- Braking system at collection drawer.
- · Coffee bean grinder assembly (own module).
- Easy cleaning and maintenance of removable elements.

STRUCTURE

- Tempered glass front embedded in metal, with no access to the sides.
- · Smudge-proof stainless steel finishing.
- Steel cabinet treated against corrosion and rust and vandal-proof lock with a crowbar-resistant door integrated into the structure.

CREDIT MANAGEMENT

• Innovative Jofemar coin mechanism with connection for both Executive and MDB protocols, five return tubes and T-15 coin validator with the most reliable fraud-prevention systems.

PROGRAMMING

- General on site programming through the machine's keyboard, EasyFlash hand terminal, PC or modem by telemetry using the Jofemar Vending Track management software.
- Data storage and stock control and accounting.

OPTIONS

- Self-feeding water kit (one or two 25L tanks, in the G546 model).
- Coffeemar Bluetec G546 Master fitted to be connected to a Vision ES or ES Plus Vending machine.
- Screen on the upper part of the G546 model for videos and nutritional facts.
- Water filters: anti-scale or flavour.
- · Card and banknote payment systems.
- Telemetry by GSM or GPRS modem using Jofemar
- Vending Track software.
- Customisable image.



A new dimension in which the image of the POS and the product quality are combined to completely satisfy the customer.



	COFFEEMAR BLUETEC G335	COFFEEMAR BLUETEC G546	COFFEEMAR BLUETEC G546 MASTER	
Services	300	500	500	
Canisters	5+beans	6+beans	6+beans	
Selections+preselection	18+3	18+3	18+3	
Whippers	3	4	4	
Graphic display	92 x 53 mm	92 x 53 mm	92 x 53 mm	
Size	1,500 x 500 x 575 mm	1,825 x 600 x 575 mm	1,825 x 600 x 575 mm	
Weight	100 kg	140 kg	140 kg	
Mains water supply	3/4 GAS			
Energy supply	230 V, 50 Hz*			
Maximum power	1,100 watts			
Estimated energy consumption	1.02 Kwh/24 h. idle	1.21 Kwh/24 h. idle	1.21 Kwh/24 h. idle	
Satelitte vending machines	No	No	Yes	

* Check for other voltages



DISTRIBUTOR

WITHOUT ELECTROVALVES



PRESSURE VALVE IN THE BREWING UNIT





KEYBOARD

TOUCH



SMUDGE-PROOF STAINLESS STEEL



Technological Innovation

Reliability

100% Jofemar

Technology

Jofemar

Ctra. Marcilla km 2 31350 PERALTA. Navarra SPAIN Tel. +34 948 75 12 12 Fax +34 948 75 04 20 **www.jofemarvending.com**











COFFEEMAR G546

COFFEEMAR G546 MASTER

COFFEEMAR G250



OPTIMISED CAPACITY AND VOLUME







Coffeemar 🛞

A break full of flavour

The Coffeemar range of hot beverages machines is the only one in the market with a pressure valve in the brewing unit to keep constant pressure during the brewing cycle. This allows extracting all the aroma and flavour of the coffee beans from the first to the last drop. Features an aluminium boiler and a motorised water distributor, eliminating most of the electrovales, thus reducing the maintenance costs and making the operation easier.

FEATURES

- Pressure valve in the brewing unit to keep constant pressure during the complete brewing cycle.
- Aluminium boiler with resistor and capped probes, with no contact with the water (avoiding o-rings and calcium oxide formation).
- Two cup-dispenser models, depending on the cup diameter (65-67 mm or 67-69 mm).
- Adjustable stir-stick dispenser, between 75 mm and 115 mm long.
- Self-cleaning of mixing bowls, product exit and grinder assembly: manual or automatic (programmable).
- Anti-steam sugar-adding system directly into the cup.
 Constant temperature control of the water in the
- boiler.
- Motorised water distributor without electrovalves.Braking system at collection drawer.
- Coffee bean grinder assembly (own module).
- Easy cleaning and maintenance of removable elements.

STRUCTURE

- Steel cabinet treated against rust and vandal-proof lock with crowbar-resistant door integrated into the cabinet.
- 92 x 53 mm graphic display.

CREDIT MANAGEMENT

• Innovative Jofemar coin mechanism with connection for both Executive and MDB protocols, five return tubes and coin validator with the most reliable fraud-prevention systems.

PROGRAMMING

- General on site programming with the machine's keyboard, EasyFlash hand terminal, PC or modem by telemetry using the Jofemar Vending Track management software.
- Data storage and stock control and accounting.

OPTIONS

- Self-feeding water kit (one or two 25L tanks, in the G546 model).
- Screen on the upper part of the G546 model for videos and nutritional facts.
- Water filters: anti-scale or flavour.
- Telemetry by GSM or GPRS modem using Jofemar Vending Track software.
- Jofemar banknote reader.
- Jofemar J130 card/key reader or any card reader that uses the MDB protocol.
- Satelitte vending machine for the model Coffeemar G546 Master.



Coffee, tea, chocolate... Hot beverages taste better in the Coffeemar range of machines. Enjoy the full flavour of a good coffee during your breaks.



	COFFEEMAR G546	COFFEEMAR G546 MASTER	COFFEEMAR G250
Services	500	500	250
Canisters	6+beans	6+beans	5+beans
Selections+preselection	20+1	20+1	15+1
Whippers	4	4	3
Illuminated panel	329.5 x 273.5 mm	329,5 x 273,5 mm	255 x 248 mm
Graphic display	92 x 53 mm	92 x 53 mm	92 x 53 mm
Size	1,825 x 600 x 561 mm	1.825 x 600 x 561 mm	1,500 x 500 x 561 mm
Weight	140 kg	140 kg	100 kg
Mains water supply	3/4 GAS		
Energy supply	230 V, 50 Hz*		
Maximum power	1,100 watts		
Estimated energy consumption	1.01 Kwh/24h. idle state	1.01 Kwh/24h. idle state	0.95 Kwh/24h. idle state
Satelitte vending machines	No	Yes	No

*Check for other voltages.



MOTORISED WATER DISTRIBUTOR WITHOUT ELECTROVALVES



EASY CLEANING AND MAINTENANCE OF REMOVABLE ELEMENTS



ALUMINIUM

BOILER

PRESSURE VALVE IN THE BREWING UNIT



Technological Innovation

Reliability

100% Jofemar

Technology

Jofemar

Ctra. Marcilla km 2 31350 PERALTA. Navarra SPAIN Tel. +34 948 75 12 12 Fax +34 948 75 04 20 **www.jofemarvending.com**



