



Snack & Food



# SNAKKY MAX FOOD





SNACKY MAX FOOD is capable of dispensing a large number of snacks, and at the same time is fitted with fresh food products disposed on a minimum of 2 till a maximum of 4 trays, which maintain a temperature lower than 4°C, while the three upper trays are reserved to snack products with a temperature between 8° and 15°C. The Snakky Max Food machine is suitable also for operation under normally adverse environmental conditions.

The anti-condensation system ensures optimum visibility of the products with a maximum external temperature of 32°C and 65% relative humidity. Furthermore, the anticondensation system also eliminates moisture from the product dispensing compartment. Thanks to the proper kit it is possible to dispense bread sticks 22.5 to 30 cm long, in addition to the standard triangular sandwiches.



Product-holders with adjustable width

### USER INTERFACE

Offering optimum product visibility for easy identification of the items and simple selection, via the numeric keypad. Is possible to programme the selection numbers of the numeric keypad to allow virtual selections and FIFO selections. FIFO modality allows an uniform emptying of the machine, a frontal machine always full and an optimal temperature of the products.

- Slightly tilted blue alphanumeric display with 4 lines and 20 characters
- Sound signal at the end of the product dispensing sequence
- Ergonomic compartment which opens outward to ensure easy access to the dispensed product - even with one hand.

### SAFETY DEVICE

To guarantee the conservation of the products in the food area, a temperature safety block has been included in the software of the machine.

### ELECTRONIC CONTROL

- 16-bit electronic control with incorporated Flash EPROM
- Automatic setup and reading of statistics with Flash application or Up-Key
- Remote monitoring via GSM technology (with proper kit)

### PAYMENT SYSTEMS

The payment systems and the electronic board are located inside a separate compartment, with independent access and slide-out opening for complete extraction, allowing work to take place in this area without affecting the temperature inside the product compartment. Snakky Max Food is pre-set for the installation of systems with Executive and MDB protocol, as well as validators. At the same time, the following can be installed:

- Change-giver coin mechanism/validator
- Bill validator
- Cashless system with key or card

### ACCESSORIES

- Kit to block dispensing compartment
- Photocell kit (standard)
- Master/slave kit
- Bidirectional drawer motors kit
- Coin box cover kit
- Wall mounting bracket kit
- RS232 jack kit
- GSM kit

INDICATIVE CONSUMPTION	
For each hour of stand-by	266 Wh
Ambient temperature	20°C
Refrigerated box temperature	3,5°C

CHARACTERISTICS	
Height	1830 mm*
Width	735 mm
Depth	855 mm
Overall depth with door open	1350 mm
Weight	225 kg ca.
Power supply voltage	230 V
Power supply frequency	50 Hz
Installed power	560 W
Refrigerant	R134a
Maximum operating conditions	32°C - 65% U. R.

\*+10 - 10 mm

CONFIGURATIONS																																																					
<b>CONFIGURATION No. 1</b>	<b>CONFIGURATION No. 2</b>																																																				
<b>3 snack trays</b> 15 selections / 156 products <b>3 food trays</b> 12 selections / 72 products	<b>4 snack trays</b> 18 selections / 194 products <b>3 food trays</b> 18 selections / 108 products																																																				
<table border="1"> <tr><td>8</td><td>8</td><td>8</td><td>160 mm</td></tr> <tr><td>13</td><td>13</td><td>11</td><td>160 mm</td></tr> <tr><td>10</td><td>10</td><td>10</td><td>178 mm</td></tr> <tr><td>6</td><td>6</td><td>6</td><td>198 mm</td></tr> <tr><td>6</td><td>6</td><td>6</td><td>172 mm</td></tr> <tr><td>6</td><td>6</td><td>6</td><td>172 mm</td></tr> </table>	8	8	8	160 mm	13	13	11	160 mm	10	10	10	178 mm	6	6	6	198 mm	6	6	6	172 mm	6	6	6	172 mm	<table border="1"> <tr><td>8</td><td>8</td><td>8</td><td>120 mm</td></tr> <tr><td>8</td><td>8</td><td>8</td><td>108 mm</td></tr> <tr><td>15</td><td>15</td><td>11</td><td>110 mm</td></tr> <tr><td>13</td><td>13</td><td>13</td><td>105 mm</td></tr> <tr><td>6</td><td>6</td><td>6</td><td>218 mm</td></tr> <tr><td>6</td><td>6</td><td>6</td><td>212 mm</td></tr> <tr><td>6</td><td>6</td><td>6</td><td>116 mm</td></tr> </table>	8	8	8	120 mm	8	8	8	108 mm	15	15	11	110 mm	13	13	13	105 mm	6	6	6	218 mm	6	6	6	212 mm	6	6	6	116 mm
8	8	8	160 mm																																																		
13	13	11	160 mm																																																		
10	10	10	178 mm																																																		
6	6	6	198 mm																																																		
6	6	6	172 mm																																																		
6	6	6	172 mm																																																		
8	8	8	120 mm																																																		
8	8	8	108 mm																																																		
15	15	11	110 mm																																																		
13	13	13	105 mm																																																		
6	6	6	218 mm																																																		
6	6	6	212 mm																																																		
6	6	6	116 mm																																																		
<span style="display: inline-block; width: 15px; height: 15px; background-color: yellow; border: 1px solid black;"></span> Snack <span style="display: inline-block; width: 15px; height: 15px; background-color: blue; border: 1px solid black; margin-left: 20px;"></span> Food																																																					
The numbers in the table indicate the product capacity																																																					



**N&W GLOBAL VENDING S.p.A.**  
 Via Roma, 24  
 24030 Valbrembo (BG) Italy  
 Ph. +39 035 606111 - Fax +39 035 606519



www.nwglobalvending.com